


Scan To Slot


All Slotting operations require Checkpoint to be in Query mode.




Scanning Volumes To Slots Using Zone, Slot and Volume Barcodes

This method relies on both the zones and slots being barcoded (further information on printing barcodes can be found [here](#)). Slotting on the repository also need to be disabled if you have the slotting allocation script being run by the scheduler or volumes will be automatically allocated a slot based on the slotting mode of that repository.


From the customer tree right click the required customer/s and select Add to load volumes into the **To Scan** window.



Once all volumes required have been added to the **To Scan** window, select Process→Special Operations→Scan To Slot from the main menu to open the scan window.



Enter the number 2 into the scan window to set scan mode to **Zone, slot and volume**.



Scan **Zone** barcode, **Slot** barcode and then the **Volume** barcode.

Checkpoint will now ask you to confirm the slot and volume by rescanning the volume barcode. If the same volume barcode is scanned the volume will be allocated to that slot.

Scan to Slot

000001L5

Barcode

Customer

Media Type

Volume-ID

Message

000001L5

Nashville Data Center

000001L5

Request OK

000001L5

Nashville Data Center

000001L5

Request OK

-S000001

Location Scan Entered

-Z00001

Location Scan Entered

2

Contol Scan entered

While still allocating volumes in the selected zone, subsequent scans only require scanning the next slot and volume and then scanning the volume again to confirm the slot allocation.



Scanning to slot only allocates the volumes to the selected slots, volumes will still need to be scanned into the repository/slots to confirm the volumes to that location.

Scan to Set Slot Allocation Flag

Using this method enables you to control the Slot allocation order of volumes, based on the order you scan them in.

This process requires the **Do not slot** option to be enabled for the Target Repository and the executable [TMSS10SlotAllocation](#) to be run either manually after scanning [Volumes](#) or scheduled on a regular basis so that it runs after scanning to set Slot allocation flag and before scanning in to the Slots to confirm.

As [Volumes](#) are placed in a move to the [Repository](#), a **t** flag will be assigned. This **t** flag stops the slotting.bat script automatically assigning a Slot.

Volumes									
ID	Current Location	Target Location	Flags	Move Time	Due in	Container	Next Move		
Enter text h...	Enter text h...	Enter text he...	Enter ...	Enter t...	Enter t...	Enter t...	Enter ...	Enter ...	Enter ...
000001L5	Library	Offsite Vault	CMnt	M1:16	Unspecified	Unassigned	Permanent		
000002L5	Library	Offsite Vault	CMnt	M1:16	Unspecified	Unassigned	Permanent		
000003L5	Library	Offsite Vault	CMnt	M1:16	Unspecified	Unassigned	Permanent		
000004L5	Library	Offsite Vault	CMnt	M1:16	Unspecified	Unassigned	Permanent		
000005L5	Library	Offsite Vault	CMnt	M1:16	Unspecified	Unassigned	Permanent		
000006L5	Library		Cn		Unspecified	Unassigned	Permanent		
000007L5	Library		Cn		Unspecified	Unassigned	Permanent		
000008L5	Library		Cn		Unspecified	Unassigned	Permanent		
000009L5	Library		Cn		Unspecified	Unassigned	Permanent		
000010L5	Library		Cn		Unspecified	Unassigned	Permanent		

When the **Volumes** arrive at the **Repository**, after loading the required **Media** into the **To Scan** window, selecting Process→Special Operations→Scan to Set Slot Allocation Flag to open the **Scan** window.

Scan the **Volumes** in the order you want the Slots to be assigned and, when all **Volumes** have been scanned, close the **Scan** window. Select Process→Update Server to update the Slot allocation flags on the scanned volumes.

Either wait the required time (depending on how often you have the Slotting.bat file scheduled to run) or run the script manually if required.

Update the Checkpoint tree by selecting Process→Build/Update Movement Tree from the main menu. Add required moving media back into the **To Scan** window, which will now display the allocated Slots for the **Volumes**.

Open the **Scan** window to scan-in the **Volumes**.

Ensure the default **Customer-ID** and **Media-ID** on the right of the **Scan** window are correct.

Enter in the required scan mode:

- Enter **0** for scanning **Volumes** barcode only.
- Enter **1** for scanning Zone and **Volumes** barcodes.
- Enter **2** for Zone, Slot and **Volumes** barcodes.

Scan in the **Volumes** as per normal operations to confirm **Volumes** into their assigned Slots.

From:

<https://docs.tapetrack.com/> - TapeTrack Documentation

Permanent link:

https://docs.tapetrack.com/checkpoint/scan_to_slot?rev=1553482268

Last update: **2025/01/21 22:07**

