Command Line Server Argument

The `logonstring` argument sets the Server logon information in the format `user:password@server:port`.

In the event that this argument is not passed the default will be `batch:batch@localhost:5000`.

In addition to the default values, these values have default behaviors as follows:

- By default the password value will be treated as the path to a file which contains a single record representing the password, rather than the password itself.
- If you wish the password value to be the literal password (rather than a file) the password should be prepended with a dash (`jsmith:-mypassword@server`).
- You can also have the program read the password as the first record of `stdin` by prepending the password with a plus symbol (`jsmith:+@server`).

In the event that the password is all upper case and 32 characters in length, the password will be considered an MD5 hash of the password and passed to the server without subsequent MD5 hashing.

Environmental Variables

- TMSSPWPATH

Examples

Connect to `localhost` with User-ID batch, password in file `c:\tapetrack\pw\batch` on port **5000**.

<sxh plain;> -S localhost </sxh>

Connect to `tapetrack.gazillabyte.com` with User-ID jsmith and prompt for the password on port **443**.

<sxh plain;> -S jsmith:+@tapetrack.gazillabyte.com:443 </sxh>

Connect to `tapetrack.gazillabyte.com` with User-ID jsmith and password of mypassword on port **443**.

<sxh plain;> -S jsmith:-mypassword@tapetrack.gazillabyte.com:443 </sxh>

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/cli/server_argument?rev=1553707750

Last update: **2025/01/21 22:07**