

TapeTrack Sync Fields

Field	Max	Description
CONTAINER	20	Fully qualified Container barcode
CUSTOMER	4	Customer-ID
DATACLUSTER	256	Data Cluster Value (Data Cluster must already exist)
DESCRIPTION	256	Volume Description (use program flag to set Extended Attributes)
ENCRYPTED	10	Is Volume encrypted (YES, NO, TRUE, FALSE)
EXPIRYDATE		
GENERATION		
HIDDEN		
HOMEREPOSITORY		
HOMESLOT		
MEDIA	4	Media-ID
MOVEDATE	64	Move Date (must have SetMoveDateFormat defined)
MOVELOCK		
QUALITYCHECK		
READTIME		
REPOSITORY	4	Repository-ID
REPOSITORY_DESC	20	Description of Repository (will be used to set the REPOSITORY field)
SCRATCH	10	Is Volume scratch (YES, NO, TRUE, FALSE)
SLOT	10	Slot for Repository.
STAGE		
STOCKID		
SYSTEM	10	System this Volume belongs to
USAGE		
USAGECOUNT		
VOLUME	10	Volume-ID
WRITETIME	64	Write Time (must have SetWriteTimeFormat defined)

Addition Sync Fields

Addition Sync fields that can be used to extract data into for comparison when using Translation statements. These are not fields that can be set directly in TapeTrack.

Field
User1
User2
User3
User4
User5
User6
User7
User8
User9

From:

<https://docs.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

https://docs.tapetrack.com/cli/sync_fields?rev=1625450511

Last update: **2025/01/21 22:07**

