

# TapeTrack Sync Fields

| Field           | Max | Description                                                          |
|-----------------|-----|----------------------------------------------------------------------|
| CONTAINER       | 20  | Fully qualified Container barcode                                    |
| CUSTOMER        | 4   | Customer-ID                                                          |
| DATACLUSTER     | 256 | Data Cluster Value (Data Cluster must already exist)                 |
| DESCRIPTION     | 256 | Volume Description (use program flag to set Extended Attributes)     |
| ENCRYPTED       | 10  | Is Volume encrypted (YES, NO, TRUE, FALSE, 0, 1)                     |
| EXPIRYDATE      |     |                                                                      |
| GENERATION      |     | Set Volume generation                                                |
| HIDDEN          |     | Is Volume Hidden (YES, NO, TRUE, FALSE, 0, 1)                        |
| HOMEREPOSITORY  |     | Set Home Repository                                                  |
| HOMESLOT        | 10  | Set Home Slot                                                        |
| MEDIA           | 4   | Media-ID                                                             |
| MOVEDATE        | 64  | Move Date (must have SetMoveDateFormat defined)                      |
| MOVELOCK        |     | Add or Remove Move Lock                                              |
| QUALITYCHECK    |     |                                                                      |
| READTIME        |     | Last Read time of Volume                                             |
| REPOSITORY      | 4   | Repository-ID                                                        |
| REPOSITORY_DESC | 20  | Description of Repository (will be used to set the REPOSITORY field) |
| SCRATCH         | 10  | Is Volume scratch (YES, NO, TRUE, FALSE 1, 0)                        |
| SLOT            | 10  | Slot for Repository.                                                 |
| STAGE           | 1   | Volume stage (0 = No Selection, 1 = Ordered, 2 = Used, 3 =Destroyed) |
| STOCKID         |     |                                                                      |
| SYSTEM          | 10  | System this Volume belongs to                                        |
| USAGE           |     |                                                                      |
| USAGECOUNT      |     | Add Usage count                                                      |
| VOLUME          | 10  | Volume-ID                                                            |
| WRITETIME       | 64  | Write Time (must have SetWriteTimeFormat defined)                    |

## Addition Sync Fields

Addition Sync fields that can be used to extract data into for comparison when using Translation statements. These are not fields that can be set directly in TapeTrack.

| Field |
|-------|
| User1 |
| User2 |
| User3 |
| User4 |
| User5 |
| User6 |
| User7 |
| User8 |
| User9 |

From:

<https://docs.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

[https://docs.tapetrack.com/cli/sync\\_fields?rev=1625615140](https://docs.tapetrack.com/cli/sync_fields?rev=1625615140)

Last update: **2025/01/21 22:07**

