

TapeTrack Sync Fields

Field	Max	Description
CONTAINER	20	Fully qualified Container barcode
CUSTOMER	4	Customer-ID
DATACLUSTER	256	Data Cluster Value (Data Cluster must already exist)
DESCRIPTION	256	Volume Description (use program flag to set Extended Attributes)
ENCRYPTED	10	Is Volume encrypted (YES, NO, TRUE, FALSE, 0, 1)
EXPIRYDATE		
GENERATION		Set Volume generation
HIDDEN		Is Volume Hidden (YES, NO, TRUE, FALSE, 0, 1)
HOMEREPOSITORY		Set Home Repository
HOMESLOT	10	Set Home Slot
MEDIA	4	Media-ID
MOUNTTIME		Last mount time
MOVEDATE	64	Move Date (must have SetMoveDateFormat defined)
MOVELOCK		Add or Remove Move Lock
QUALITYCHECK		
READTIME		Last Read time of Volume
REPOSITORY	4	Repository-ID
REPOSITORY_DESC	20	Description of Repository (will be used to set the REPOSITORY field)
SCRATCH	10	Is Volume scratch (YES, NO, TRUE, FALSE 1, 0)
SLOT	10	Slot for Repository.
STAGE	1	Volume stage (0 = No Selection, 1 = Ordered, 2 = Used, 3 =Destroyed)
STOCKID		
SYSTEM	10	System this Volume belongs to
USAGE		
USAGECOUNT		Add Usage count
VOLUME	10	Volume-ID
WRITETIME	64	Write Time (must have SetWriteTimeFormat defined)

Addition Sync Fields

Addition Sync fields that can be used to extract data into for comparison when using Translation statements. These are not fields that can be set directly in TapeTrack.

Field
User1
User2
User3
User4
User5
User6
User7
User8

Field
User9

From:
<https://docs.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/cli/sync_fields?rev=1640837138

Last update: **2025/01/21 22:07**

