

TMSS10BatchLoader

Synopsis

TMSS10BatchLoader [-c configuration file] [-S logonstring]

Description

Creates Customer, Media and Repositories by loading a configuration file into the TapeTrack Database.

Options

- -c The config file argument specifies the path to the Batch Configuration File.
- -S Logon string argument sets the [Server logon information](#).

Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff. If you are experiencing problems or want some advice on how to configure or use the product please see the [Accessing Technical Support](#) page.

Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

Environment

Files

Example

Headline

Configuration file to load to create two Customers with duplicate attributes

- Customer ID: 0001, Customer Description: ACME Computers
- Customer ID: 0002, Customer Description: Bond Corporation

with two media types

- Media ID: LTO, Media Description: LTO Cartridge
- Media ID: 3490, Media Description: IBM 3490 Cartridge.

and two repositories

- Repository ID: LIBR, Repository Description: Library, Repository Type: 1, Next Repository: OFFS
- Repository ID: OFFS, Repository Description: Iron Mountain, Repository Type: 2 and Next Repository: LIBR.

<sxh> setup= {

```
customers=
(
  {
    id="0001"; description="ACME Computers";
```

```
    media=
    (
      {
        id="LTO"; description="LTO Cartridge";
```

```
      repositories=
      (
        { id="LIBR"; description="Library"; type=1; },
        { id="OFFS"; description="Iron Mountain"; type=2; }
      )
    },
    {
      id="3490"; description="IBM 3490 Cartridge";
```

```
      repositories=
      (
        { id="LIBR"; description="Library"; type=1; next="OFFS"; },
        { id="OFFS"; description="Iron Mountain"; type=2; }
      ),
      next="LIBR"; }
    )
  },
  {
    id="0002"; description="Bond Corporation";
```

```
    media=
    (
      {
        id="LTO"; description="LTO Cartridge";
```

```
    repositories=
```

```
(
    { id="LIBR"; description="Library"; type=1; },
    { id="OFFS"; description="Iron Mountain"; type=2; }
)
},
{
    id="3490"; description="IBM 3490 Cartridge";
```

```
repositories=
(
    { id="LIBR"; description="Library"; type=1; },
    { id="OFFS"; description="Iron Mountain"; type=2; }
)
}
)
}
);
```

```
}; </sxh>
```

Command line syntax

```
<sxh>TMSS10BatchLoader -S user:-password@localhost -c master.cfg</sxh>
```

From:

<https://docs.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://docs.tapetrack.com/cli/tmss10batchloader?rev=1551053304>

Last update: **2025/01/21 22:07**

