TMSS10IRM_Reconcile

Synopsis

```
TMSS10IRM_Reconcile [-I iron mountain accounts] [-S logon string] [-U date format] [-m customer mapping file] [-n number of records to skip]
```

Description

Processes an Iron Mountain inventory file and produces a TapeTrack scan file to be used for reconciliation.

Options

- `-I` Iron Mountain account inclusions (default = *)
- `-S` The logon string argument sets the Server logon information.
- `-U` Dates are in MMDDYYYY (US) format not DDMMYYY (default = false)
- `-m` Customer Mapping File, used to map Iron Mountain account numbers to TapeTrack customer-ID's (default = NULL)
- `-n` Number of records at beginning of Inventory File to skip=1

Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff. If you are experiencing problems or want some advice on how to configure or use the product please see the Accessing Technical Support page.

Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

Environment

Files

stdout: Output Reports.
stderr: Diagnostic messages.

stdin: Program input.

Example

Command line syntax

<sxh> TMSS10IRM_Reconcile -S user:-password@server -U -m “mapping.txt” </sxh>

Output

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/cli/tmss10irm_reconcile?rev=1527216307

Last update: **2025/01/21 22:07**