# TMSS10ListUsage

TMSS10ListUsage produces a report on Volume Health.

## Synopsis

```
TMSS10ListClients [-R date range] [-S logon string] [-V volume filter]
```

## Options

- -R Specifies the date range.
- -S The Logon string argument sets the Server Logon Information.
- -V Volume Filter which can be used to filter the traversal of Customer, Media, Volume, Repository and Flag values.

If an argument value starts with the value `FI:`, the value for that attribute will be read from the file name specified immediately after it. For example, if a file named ACME_volumes has the content `ACME_*.*`, specifying `FI:/etc/ACME_volumes` will have the same effect as `-V ACME.*.*`. Using `FI:` to refer to a file for an attribute value works for all attributes.

If the pattern being matched starts with *LIST: then rather than matching the literal value, each record in the file specified as *LIST:filename will be tested. If one matches the match will succeed.

2025/01/21 22:08
include page

### Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff.

If you are experiencing problems or want some advice on how to configure or use the product please see the Accessing Technical Support page.

### Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

### Environment

### Files

**stdout:** Output Reports.
**stderr:** Diagnostic messages.
**stdin:** Program input.

# Example

### Command line syntax

```
TMSS10ListUsage -S user:-password@server  -R "M-3:m-3"
```

### Output

```
```

Changelog
Cannot load rss feed.

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
**https://docs.tapetrack.com/cli/tmss10listusage?rev=1653967606**

Last update: **2025/01/21 22:07**