TMSS10ListUsage

TMSS10ListUsage produces a report on Volume Health.

Synopsis

```
TMSS10ListClients [-R date range] [-S logon string] [-V volume filter]
```

Options

- -R Specifies the date range.
- -S The Logon string argument sets the Server Logon Information.
- -V Volume Filter which can be used to filter the traversal of Customer, Media, Volume, Repository and Flag values.

If an argument value starts with the value `FI:`, the value for that attribute will be read from the file name specified immediately after it. For example, if a file named ACME_volumes has the content `ACME_*.*`, specifying `FI:/etc/ACME_volumes` will have the same effect as `-V ACME.*.*`. Using `FI:` to refer to a file for an attribute value works for all attributes.

If the pattern being matched starts with *LIST: then rather than matching the literal value, each record in the file specified as *LIST:filename will be tested. If one matches the match will succeed.

2025/01/21 22:08
include page

Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff.

If you are experiencing problems or want some advice on how to configure or use the product please see the Accessing Technical Support page.

Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

Environment

Files

stdout: Output Reports.
stderr: Diagnostic messages.
stdin: Program input.

Example

Command line syntax

```
TMSS10ListUsage -S user:-password@server  -R "M-3:m-3"
```

Output

```
```

Changelog
: Cannot load rss feed.

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/cli/tmss10listusage?rev=1737497272

Last update: **2025/01/21 22:07**