# TMSS10ModifyFlags

## Synopsis

```
TMSS10ModifyFlags [-F new flags] [-S logon string] [-V volume filter] [-c
configuration file]
```

## Description

TMSS10ModifyFlags adds and removes editable flags through the command line interface.

## Options

- -F Adds or removes flags from volumes.
- -S The logon string argument sets the Server logon information
- -V Volume Filter which can be used to filter the traversal of Customer, Media, Volume, repository and flag values.
- -c The config file argument specifies the path to the Batch Configuration File. The Batch Configuration File allows you to perform advanced traversal of Customer, Media and Volumes, perform advanced barcode pre and post processing and route program output to syslogd.

### Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff. If you are experiencing problems or want some advice on how to configure or use the product please see the Accessing Technical Support page.

### Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

### Files

**stdout:** Output Reports.
**stderr:** Diagnostic messages.

## Example

**Command line syntax**

<sxh plain;> TMSS10ModifyFlags -S user:-password@server -V “*US04.LTO.*@OFFS” -F E </sxh>

**Output**

<sxh plain;>

```
           System: TapeTrack
```

Report Description: Flag Modification Report

```
  Production Time: Friday, April 20, 2018 - 09:43:19 (AUS Eastern Standard
Time)
     Report Width: 156 bytes
```

Seq. Barcode Old Flags New Flags Message —— ———————– ———————————– ———————————– ——————–

```
    1 US04.LTO.000005L6    CnNOtZ                              CEnNOtZ
Request OK
    2 US04.LTO.000006L5    CnNOt                               CEnNOt
Request OK
    3 US04.LTO.000006L6    CnNOt                               CEnNOt
Request OK
    4 US04.LTO.000007L5    CnNOt                               CEnNOt
Request OK
    5 US04.LTO.000007L6    CMnNt                               CEMnNt
Request OK
    6 US04.LTO.000008L5    CMnNt                               CEMnNt
Request OK
    7 US04.LTO.000009L5    CnNOt                               CEnNOt
Request OK
    8 US04.LTO.000009L6    CnNOt                               CEnNOt
Request OK
```

—— ———————– ———————————– ———————————– ——————– </sxh>

# Example

To remove the Warning flag (W) you would use: <sxh plain;> TMSS10ModifyFlags -S tapemaster:-password@localhost -F “!W” </sxh>

Substitute your password for the password value.

A **!** means remove the flag. Without an **!** it will be added.

To set the encrypted flag on all LTO tapes:

<sxh plain;> TMSS10ModifyFlags -S tapemaster:-password@localhost -F “E” -V “*.LTO.*” </sxh>

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
**https://docs.tapetrack.com/cli/tmss10modifyflags?rev=1524181572**

Last update: **2025/01/21 22:07**