TMSS10Reconcile

TMSS10Reconcile performs a batch reconciliation on a Repository.

Synopsis

```
TMSS10Reconcile [-B bypass confirmation] [-C certify] [-F don't fix surplus volumes] [-R Subject repository] [-S logon string] [-V volume filter] [-a add fully qualified volumes] [-c configuration file] [-d certificate description] [-e csv error file location] [-l input scan list] [-m minimum loaded volumes to continue]
```

Options

- `-A` Attribute Index (default=0)
- `-B` Bypass confirming Volume at Target Repository.
- `-C` Certify Volumes (default = false).
- `-F` Don't fix surplus Volumes by moving them to the Scan Repository and back (default = false).
- `-G` Number of grace hours on confirmed Volumes before audit flag added (default = 24 hours)
- `-R` Subject Repository for reconciliation.
- `-S` The Logon string argument sets the Server Logon Information.
- `-V` Volume Filter which can be used to filter the traversal of Customer, Media, Volume, Repository and flag values.
- `-a` Add any fully qualified Volume in the scanfile not in TapeTrack (default = false).
- `-c` The config file argument specifies the path to the Batch Configuration File. The Batch Configuration File allows you to perform advanced traversal of Customer, Media and Volumes, perform advanced Barcode pre and post processing and route program output to syslogd.
- `-d` Certificate description.
- `-e` CSV error file location.
- `-l` Input scan file list to reconcile against.
- `-m` Minimum loaded Volumes to continue to execute process (default = 10).

If an argument value starts with the value `FI:`, the value for that attribute will be read from the file name specified immediately after it. For example, if a file named ACME_volumes has the content `ACME_*.*`, specifying `FI:/etc/ACME_volumes` will have the same effect as `-V ACME.*.*`. Using `FI:` to refer to a file for an attribute value works for all attributes.

If the pattern being matched starts with *LIST: then rather than matching the literal value, each record in the file specified as *LIST:filename will be tested. If one matches the match will succeed.

2025/01/21 22:08
include page

Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff. If you are experiencing problems or want some advice on how to configure or use the product please see the Accessing Technical Support page.

Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

Environment

Files

stdout: Output Reports.
stderr: Diagnostic messages.
stdin: Program input.

Example

Command line syntax

```
TMSS10Reconcile -S user:-password@server -R "OFFS" -l
"C:\Users\GazillaByte\reconcile_2017-11-29.txt" -V "US04.LTO.*"
```

Output

The output of the TapeTrack Reconciliation program is described in detail on the page Reconciliation Report

Changelog
Cannot load rss feed.

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/cli/tmss10reconcile?rev=1737497272

Last update: **2025/01/21 22:07**