TMSS10ValidateBarcode

Synopsis

```
TMSS10ValidateBarcode [-C customer ID] [-M media ID] [-S logon string]
```

Description

TMSS10ValidateBarcode will parse a list of volume barcodes, outputting the barcode rule the barcode will be parsed under if valid.

Options

- -C Default Customer ID.
- -M Default Media ID
- -S The logon string argument sets the Server logon information

Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff. If you are experiencing problems or want some advice on how to configure or use the product please see the Accessing Technical Support page.

Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

Environment

Files

stdout: Output Reports.
stderr: Diagnostic messages.
stdin: Program input.

Example

Command line syntax

```
TMSS10ValidateBarcode -S user:-password@server -C "US02" -M "LTO"
```

Output

```
             System: TapeTrack
 Report Description: Barcode Parse Report
    Production Time: Monday, November 27, 2017 - 11:18:23 (AUS Eastern
Daylight Time)
       Report Width: 157 bytes

 Seq.   Barcode              C-ID M-ID V-ID       Rule Rule Description
Result
 ------ -------------------- ---- ---- ---------- ---- --------------------
------------
111111L6
      2 111111L6             US02 LTO  111111L6     18 Generic *
Request OK
1234567890L6
      3 1234567890L6         US02 LTO  1234567890   18 Generic *
Request OK
```



Note the truncation of volume barcodes over 10 characters.

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/cli/tmss10validatebarcode?rev=1511742055

Last update: **2025/01/21 22:07**