

TMSS10ValidateBarcode

Synopsis

TMSS10ValidateBarcode [-C Customer-ID] [-M Media-ID] [-S logon string]

Description

TMSS10ValidateBarcode will parse a list of volume Barcodes, outputting the Barcode rule the Barcode will be parsed under if valid.

Options

- -C Default Customer-ID.
- -M Default Media-ID
- -S The Logon string argument sets the [Server Logon Information](#)

Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff. If you are experiencing problems or want some advice on how to configure or use the product please see the [Accessing Technical Support](#) page.

Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

Environment

Files

stdout: Output Reports.

stderr: Diagnostic messages.

stdin: Program input.

Example

Command line syntax

```
<sxh plain;> TMSS10ValidateBarcode -S user:-password@server -C "US02" -M "LTO" </sxh>
```

Once you have run the above code, enter in the Barcodes to be parsed either manually, via cut and paste or Barcode scanner.

Output

```
<sxh plain;>
```

System: TapeTrack

Report Description: Barcode Parse Report

Production Time: Monday, November 27, 2017 - 11:18:23 (AUS Eastern Daylight Time)
Report Width: 157 bytes

Seq. Barcode C-ID M-ID V-ID Rule Rule Description Result
----- 111111L6

2	111111L6	US02	LTO	111111L6	18	Generic *
Request OK						

1234567890L6

3	1234567890L6	US02	LTO	1234567890	18	Generic *
Request OK						

```
</sxh>
```

Note the truncation of volume Barcodes over 10 characters.

Changelog

Cannot load rss feed.

From:
<https://docs.tapetrack.com/> - TapeTrack Documentation

Permanent link:
<https://docs.tapetrack.com/cli/tmss10validatebarcode?rev=1578528484>

Last update: 2025/01/21 22:07



