TMSS10ValidateBarcode

Synopsis

```
TMSS10ValidateBarcode [-C Customer-ID] [-M Media-ID] [-S logon string]
```

Description

TMSS10ValidateBarcode will parse a list of volume Barcodes, outputting the Barcode rule the Barcode will be parsed under if valid.

Options

- `-C` Default Customer-ID.
- `-M` Default Media-ID
- `-S` The Logon string argument sets the Server Logon Information

If an argument value starts with the value `FI:`, the value for that attribute will be read from the file name specified immediately after it. For example, if a file named ACME_volumes has the content `ACME_*.*`, specifying `FI:/etc/ACME_volumes` will have the same effect as `-V ACME.*.*`. Using `FI:` to refer to a file for an attribute value works for all attributes.

If the pattern being matched starts with *LIST: then rather than matching the literal value, each record in the file specified as *LIST:filename will be tested. If one matches the match will succeed.

2025/01/21 22:08
include page

Technical Support

The TapeTrack Software is commercially supported by a full time help desk staff. If you are experiencing problems or want some advice on how to configure or use the product please see the Accessing Technical Support page.

Exit Statuses

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

Environment

Files

stdout: Output Reports.
stderr: Diagnostic messages.
stdin: Program input.

Example

Command line syntax

```
TMSS10ValidateBarcode -S user:-password@server -C "US02" -M "LTO"
```

Once you have run the above code, enter in the Barcodes to be parsed either manually, via cut and paste or Barcode scanner.

Output

```
             System: TapeTrack
 Report Description: Barcode Parse Report
    Production Time: Monday, November 27, 2017 - 11:18:23 (AUS Eastern
Daylight Time)
       Report Width: 157 bytes

 Seq.   Barcode              C-ID M-ID V-ID       Rule Rule Description
Result
 ------ -------------------- ---- ---- ---------- ---- --------------------
------------
111111L6
      2 111111L6             US02 LTO  111111L6     18 Generic *
Request OK
1234567890L6
      3 1234567890L6         US02 LTO  1234567890   18 Generic *
Request OK
```



Note the truncation of volume Barcodes over 10 characters.

Changelog

Cannot load rss feed.

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/cli/tmss10validatebarcode?rev=1626913031

Last update: **2025/01/21 22:07**