TMSS10VolumeRename

This program renames a volume or list of volumes

Synopsis

```
TMSS10VolumeRename [-S logonstring] [-V volumefilter] [-C new Customer ID] [-M new Media ID] [-N new Volume ID] [-c configfile] [-l Live mode]
```

Description

TMSS10VolumeRename will rename the volume ID of a current volume or list of volumes, keeping history records associated with that volume/s.

Options

TMSS10VolumeRename command options:

- -S The logon string argument sets the Server logon information.
- -V The volume filter argument sets the Volume Filter which can be used to filter the traversal of Customer, Media and Volume values. The format of this filter is c.m.v@r, where c is Customer-ID filter, m is Media-ID filter, v is Volume-ID filter and r is Repository-ID filter. To process only volumes not in Repository ACME, "*.*.*@!(ACME).
- -C New Customer ID.
- -M New Media ID.
- -N New Volume ID.
- -c The config file argument specifies the path to the Batch Configuration File. The Batch Configuration File allows you to perform advanced traversal of Customer, Media and Volumes, perform advanced barcode pre and post processing and route program output to syslogd. Configuration File capabilities vary from program to program but the syntax remains the same. In the event that logic is not supported it will simply be ignored.
- -l Live mode.

Exit Status

1. **zero** Program has ended successfully.
2. **non-zero** Program has not ended successfully.

Environment

Files

- `stdout` Output Reports.
- `stderr` Diagnostic messages.

Examples

Renaming Volume - New Volume ID

Renaming Volume - Same ID, New Customer ID

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/cli/tmss10volumerename?rev=1521591409

Last update: **2025/01/21 22:07**