

Command Line Volume Filter Argument

The **Volume** filter argument sets the **Volume** Filter which can be used to filter the traversal of **Customer**, **Media** and **Volume** values. The format of this filter is `c.m.v@r+f`, where `c` is **Customer-ID** filter, `m` is **Media-ID** filter, `v` is **Volume-ID** filter, `r` is **Repository-ID** filter and `f` is the **Flag** filter.

If the `-V` filter is not assigned a value it assumes the default of `-V "*"*.*.*)"` which will, by use of wild card value, include all **Volumes**. Each of the values within the filter can be left as a wild card or assigned a value.

Examples

To process all **Volumes** only in **Repository** ACME

```
-V "*"*.*.)*@ACME"
```

To process all **Volumes** not in **Repository** ACME

```
-V "*"*.*.)*@!(ACME) "
```

To process all **LTO Volumes** for **Customer** US01

```
-V "US01.LT0.*"
```

To process all **LTO Volumes** for **Customer** US01 in repository **ACME** with an **encrypted** flag

```
-V "US01.LT0.*@ACME+E"
```

From:

<https://docs.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

https://docs.tapetrack.com/cli/volume_filter?rev=1626912622

Last update: **2025/01/21 22:07**

