Command Line Volume Filter Argument

The Volume filter argument sets the Volume Filter which can be used to filter the traversal of Customer, Media and Volume values. The format of this filter is `c.m.v@r+f`, where `c` is Customer-ID filter, `m` is Media-ID filter, `v` is Volume-ID filter, `r` is Repository-ID filter and `f` is the Flag filter.

If the -V filter is not assigned a value it assumes the default of `-V “*.*.*”` which will, by use of wild card value, include all Volumes. Each of the values within the filter can be left as a wild card or assigned a value.

Examples

To process all Volumes only in Repository ACME

```
-V "*.*.*@ACME"
```

To process all Volumes not in Repository ACME

```
-V "*.*.*@!(ACME)"
```

To process all **LTO** Volumes for Customer **US01**

```
-V "US01.LTO.*"
```

To process all **LTO** Volumes for Customer **US01** in repository **ACME** with an **encrypted** flag

```
-V "US01.LTO.*@ACME+E"
```

To process all **LTO** Volumes in the offsite Repository that are Scratch and not Encrypted.

```
-V "*.LTO.*@OFFS+Z!E"
```

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/cli/volume_filter?rev=1626912683

Last update: **2025/01/21 22:07**