

BackupExec

BackupExec is Veritas's small business backup solution and depending on the version, allows **Volume** information to be extracted via:

1. Command line, or
2. Windows Power Shell, or
3. ODBC.

When **Volumes** are new, they will appear in the Scratch Media Set, but as they are used they are assigned to a specific Media Set. Unlike Veritas's **NetBackup** product, when **Volumes** expire, by default, they are not moved back into the Scratch Media Set.

The Command Line Interface

The Command Line Interface was used in BackupExec 2010 and below.



When BackupExec is installed a number of predefined reports are created. The ID of each predefined report varies from one installation to the next.

Sample Command Line Syntax

```
<sxh> bemcmd -o402 -r25 -ft:4 -f:"BE.csv" > "BE-CMD.txt" 2>&1 </sxh>
```

The Windows Powershell interface

The Windows Powershell interface replaced the Command Line Interface in BackupExec 2012.

Sample Powershell Script

```
<sxh> cd "C:\Program Files\Symantec\Backup Exec\Modules\BEMCLI" import-module BEMCLI  
cd "C:\Program Files\TapeTrack\TapeTrack Sync\var"  
  
# # Get Media list from Backup Exec # $MediaList = Get-BEMedia $Today = Get-Date  
  
# # Initialize the output array # $Records = @()  
  
ForEach ($Media in $MediaList) {
```

```
    $Record = "" | Select-Object CartridgeLabel, MediaSetName, MediaVault,  
    RetentionHoursRemaining
```

```

$Record.CartridgeLabel = $Media.Name
$Record.MediaSetName = $Media.MediaSet
$Record.MediaVault = $Media.MediaVault
$Record.RetentionHoursRemaining = [Int]($Media.OverwriteProtectedUntilDate
- $Today).TotalHours
$Records += $Record
}

$Records | Export-CSV -notype BE.csv </sxh>

```

Synchronization



You will need to install the [TapeTrack Sync software](#) to complete these instructions.

Synchronization with TapeTrack is performed by calling the [TMSS10Sync](#) command line program, along with:

1. The CSV output file.
2. Command line arguments that instructs the program how to process volumes.
3. A synchronization definition file that instructs the program how to interpret the CSV output.

Example Command Line Arguments

Call Windows Powershell and run the BE-List script.

Call the TapeTrack Sync module and process the output created by the Powershell script.

```
<sxh> powershell.exe -NoProfile -file "BE-List.ps1" -executionpolicy RemoteSigned TMSS10Sync -S
user:-password@server -a -d BE.ttidef < BE.csv </sxh>
```

Where:

- -d is the path to the Synchronization Definition File.
- -a tells the program to add new tape volumes if they are encountered.
- -S tells the program what [Server](#) to connect to.
- BE.CSV is the output from the BE-List script.

Example Synchronization Definition

BE.ttidef

```
<sxh> # # Set the Customer and Media as literal values as they never change #
SetLiteral(CUSTOMER, "ACME"); SetLiteral(MEDIA, "LTO");
```

```
# # Set CSV delimiter # SetCSVDelimiter(",");
```

```
# # Get the Volume-ID # Extract(VOLUME, 1, 10, 0);
```

```
# # Get the Repository from a translated location Name # Extract(REPOSITORY, 0, 200, 0);  
AddTranslation(REPOSITORY, "*,WEEKLY_BACKUP*,*[0-9]*", "OFFS"); AddTranslation(REPOSITORY, "*,  
"LIBR");
```

```
# # Set the Description to the Pool Name # Extract(DESCRIPTION, 2, 100, 0);  
RemoveSpaces(DESCRIPTION); # </sxh>
```

From:

<https://docs.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://docs.tapetrack.com/cookbook/backupexec?rev=1546017394>

Last update: **2025/01/21 22:07**

