VEEAM Sync Cookbook

Veeam Backup & Replication is a software product developed by Veeam Software to back up, restore and replicate data on virtual machines

Prerequisites

A defined ODBC connection to the VEEAM database.

Data Extraction

Data is extracted from VEEAM via an SQL connection and then processing that raw data for the SYnc with TapeTrack via a ttidef file.

TTIDEF Sample

Sample TTIDEF file to:

- Connect to VEEAM database (veeam2 in this example).
- Extract barcode, media pool ID and last write time.
- Set Customer-ID to US01.
- Set Media-ID to LTO.
- Set Volume location based off media pool ID.
- Set Volume Description based off media pool ID

<sxh> # # Connect to Veeam database SetODBC(“DSN=veeam2”); # Extract data SetSQL(“SELECT [barcode],[media_pool_id],[last_write_time] FROM [VeeamBackup].[dbo].[Tape.tape_mediums]”);

Set Customer-ID SetLiteral(CUSTOMER, “US01”); # Set media to LTO as only one media type in report SetLiteral(MEDIA, “LTO”);

Set place marker for Description SetLiteral(DESCRIPTION, “????”); # Set place marker for Repository SetLiteral(REPOSITORY, “????”);

Extract Volume-ID from column 1 Extract(VOLUME, 1, 10, 0); # Extract media pool-id for translation from column 2 Extract(USER1, 2, 50, 0); # Extract last writetime from column 3 Extract(WRITETIME, 3, 50, 0);

Set writetime format SetWriteTimeFormat(“Y-m-d H:M:S”);

Add translations to set Description based off Media Pool-ID AddTranslation2(DESCRIPTION, USER1, “4C6BFE92-5C7F-BFE9-A18E-B52A8049C167”, “Alpha media pool”); AddTranslation2(DESCRIPTION, USER1, “601ED8E9-647E-A19E-B18E-F6D66B0EE584”, “Bravo media pool”); AddTranslation2(DESCRIPTION, USER1, “375TED22-7654-B34R-67GH-TMX642021SEE”, “Charlie media pool”); AddTranslation2(DESCRIPTION, USER1, “9454924F-834C-22C0-9A35-F6D44B0EE214”,

“Free Tapes”); AddTranslation2(DESCRIPTION, USER1, “3376924Q-221C-59C0-3A65-F6D32B0FW857”, “Imported”);

Add translations to set Repository based off Media Pool-ID # Move matching media pools offsite AddTranslation2(DESCRIPTION, USER1, “4C6BFE92-5C7F-BFE9-A18E-B52A8049C167”, “OFFS”); AddTranslation2(DESCRIPTION, USER1, “601ED8E9-647E-A19E-B18E-F6D66B0EE584”, “OFFS”); AddTranslation2(DESCRIPTION, USER1, “375TED22-7654-B34R-67GH-TMX642021SEE”, “OFFS”);

All other media pool place in library AddTranslation2(REPOSITORY, USER1, “*”, “LIBR”);

Stop any movement from racking back to offsite AddSkipOnRepositoryChange(“OFFS”, “RACK”, “*”); </sxh>

cookbook, veeam, sync

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/cookbook/veeam?rev=1613522908

Last update: **2025/01/21 22:07**