addstring AddString Add a special string such as an exclusion or header string. Phase This instruction is used by the TapeTrack Import Engine. Syntax AddString(type, offset, filter); string type; integer offset; string filter;

```
type    The special string type of one of the following:
```

1. HEADER A string that represents the first record of a heading section. 2. EXCLUSION A string that represents the a record that should be excluded from all further processing (skipped). 3. START A string that represents when processing should start. If there is no start string specified processing will start at the first record. 4. END A string that represents when processing should temporarily stop. Processing will recommence at the next START record. 5. TERMINATE A string that represents when processing should permanently stop. No processing will be done past this point, even if a START record is encountered.

```
offset  The zero based offset within the record at which the filter should
be applied.
filter  A filter value for comparison with the processed string.
```

Examples Example A.22. AddString: Define a header (ANSI page break) with 7 records, skip records not starting with an integer and terminate processing at the first blank record AddString(HEADER, 0, “1*”); SetHeaderCount(7); AddString(EXCLUSION, 0, “!([0-9]*”); AddString(TERMINATE, 0, “ *”);

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/engine/import/addstring?rev=1534197979

Last update: **2025/01/21 22:07**