Extract REPOSITORY field from offset 70, length 4 of the 3rd record of a header. <sxh> Extract(REPOSITORY, 70, 4, 3); </sxh>

Extract

import engine, sync engine

Extract a field from a record, CSV element or SQL field.

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/engine/importExtract?rev=1583979087

Last update: **2025/01/21 22:07**

Phase

This function is used by the TapeTrack Import Engine.

Syntax

```
Extract(field, offset, length, record);
```

Variable	Type	Description	Min Length	Max Length	Min Value	Max Value
field	String	The field to be set by this extraction.	1	128		
offset	Integer	The zero based offset of the data to be extract, or the element index of a CSV element or SQL element. In the event that the data being processed is CSV based, a value of zero indicates that the raw CSV string should be extracted rather than an individual CSV element.	1	10	-214748364	2147483647
length	Integer	The length of the data to be extracted if the data is text based, or the maximum data length for CSV or SQL data.	1	10	-214748364	2147483647
record	Integer	The record within a header, if the value is non-zero and the data is text based. A record that is not a header if the value is zero and the data is text based. For CSV and SQL data this argument is ignored.	1	10	-214748364	2147483647

Example

Extract VOLUME field from offset 10, length 6 of the body of a report. <sxh> Extract(VOLUME, 10, 6, 0); </sxh>

Extract VOLUME field from the 2nd element of a CSV file. <sxh> SetCSVDelimiter(“,”);