Lite Configuration File

The TMSSLite.cfg file allows TapeTrack administrators to customize the end-user experience for Lite users. You can insert, remove, and change the names of the tasks in the **Tape Management Task Menu**, limit functions of a Repository, and manage how log files are created and archived.

Customizing the Library Management Tasks Menu

The `menu =` command in the TMSSLite.cfg file can be used to customize the Tape Management Task Menu.

Tasks can be added, hidden, reordered, and renamed to address the specific needs of an organization or individual.




Modification of the configuration files alters settings for the local installation of TapeTrack Desktop software.

Being a local modification, means it only affects the local installation so will need to be executed on all local machines you want to alter the display on.

TMSSLite.cfg - Notepad

File Edit Format View Help


```
options=
{
   menu=
   (
      {
         filter="*Guide*";
         hidden=true;
      },
      {
         filter="*Users*";
         hidden=true;
      },
      {
         filter="*Upload*";
         hidden=true;
      },
      {
         filter="*Outlook*";
         hidden=true;
         // text="Alternate iCalendar text";
      },
      {
            hidden=true;
            text="Custom Command 1";
            //sequence=100;
            command="echo hello > out.txt";
            filters=( "*this string will be excluded*", "*So will this string*" );
      }
   );
```



There are several commands that can be used under the menu command:

- // - a double forward slash indicates a comment. Because of this, anything following a double slash will not be included in the script and will not modify TapeTrack Lite.
- **filter** - filter is used to isolate the pre-existing command that you would like to alter. TapeTrack Filters can be used in this section. For example, the above script uses “ filter=“*Outlook*”; ” to isolate any variable in the Tape Management Task Menu that has the word “Outlook” in it. Due to the fact that “Outlook Integration” is the only Tape Management Task Menu item that has “Outlook” in it, it is the only menu item that will be isolated and changed.
- **hidden** - hidden can either be true or false and will dictate whether or not a Tape Management Task Menu appears in the menu.
- **text** - text indicates what will be displayed in the Tape Management Task Menu in TapeTrack Lite.
- **sequence** - sequence indicates where in the Tape Management Task Menu menu the task will appear. The native sequence numbers are in tens. For example:

Default Menu View



In this example, Scan-In would be the first option. It thus has a sequence number of 10. Likewise, List is the sixth option and thus has a sequence number of 60. To put a custom command between Recall and Manage, you could use the number “45” in the TMSSLite.cfg file to indicate that it is between the 4th and 5th option.

- **command** - command can be used to add a command line function to the Tape Management Task Menu. The most popular of these is TMSS10Ping.

Example

The following script was used to alter the displayed menu: <sxh plain;>

```
   menu=
(
   {
       filter="*Guide*";
       hidden=true;
   },
   {
       filter="*Users*";
       hidden=true;
   },
   {
       filter="*Upload*";
```

```
        hidden=true;
    },
    {
        filter="*Outlook*";
        hidden=true;
        // text="Alternate iCalendar text";
    },
    {
           hidden=true;
           text="Custom Command 1";
           //sequence=100;
           command="echo hello > out.txt";
           filters=( "*this string will be excluded*", "*So will this
string*" );
    },
     {
         filter="*Send*";
         hidden=false;
         text="Transmit to Offsite Vault";
         sequence=01;
     },
     {
         filter="*Recall*";
         hidden=false;
         text="Return from Offsite Vault";
         sequence=02;
     },
     {
         hidden=false;
         text="Ping TapeTrack Server";
         command="TMSS10Ping localhost";
         sequence=100;
     }
 );
 </sxh>
```

The above script provides the necessary components to:

- Hide the Outlook component.
- Change the name of the **Send** function to **Transmit to Offsite Vault**.
- Place the **Send** function at the top of the drop down list.
- Change the name of the **Recall** function to **Return from Offsite Vault**.
- Place the **Recall** function second in the drop down list.
- Add a command to the Tape Management Task Menu that runs TMSS10Ping for the local TapeTrack Server with the text **Ping TapeTrack Server**.
- Place that command at a low location in the Tape Management Task Menu.
- Change the Save Location for Log Files.

Note: the sequence numbers 01 and 02 were used to indicate that they came before the default first sequence number of “10” that is typically assigned to **Scan-In**.

Modified Menu View

Log Files

Log files create a .txt read -file of all of the actions that are performed during a session. Using the TMSSLite.cfg file, you can change the location of where these files are saved. The default save location is “ %HOMEDRIVE%HOMEPATH\\Documents ”;

To change where the log file is saved uncommented (remove // at the start of line) and set directory path where you want the file written to. The directory specified must exist before running TapeTrack Lite.

<sxh plain;> logfile=“C:\Users\GazillaByte\Documents\TapeTrack Log Files”;</sxh>

Once the log file directory is specified in the configuration file, the log file location screen will no longer be displayed when selecting tasks in TapeTrack Lite.

Repository Filter

Changing the “localrepositoryfilter” variable will limit TapeTrack Lite users to only see a specific repository within their customers. You can use TapeTrack Filters to facilitate this. For example, if you added the script:

<sxh> localrepositoryfilter=“*LIBR*”; </sxh> TapeTrack Lite will only display repository IDs containing “LIBR”.

Route Log Files to a Syslogd Service

Additionally, if you have a syslogd service setup, you can use the TMSSLite.cfg file to send log files to your syslogd server using the “ syslogd = ” command. The TMSSLite.cfg sample file has the following example: <sxh>syslogd = { facility=“local1”; server=“192.168.10.1”; port=514; };</sxh>

Disable Speech

You can stop TapeTrack Lite verbalizing scanning errors by uncommenting (remove // at the start of line) the line <sxh plain;>disablespeech=true;</sxh>

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/lite/config_file?rev=1544396610

Last update: **2025/01/21 22:07**