Repository Options

GUID

Allowable Volume ID's

When left blank, volumes with any allowable characters can be added to this repository. Filters can be added to force all new volumes added to conform to certain criteria.

```
Adding ??????L? will force all new volumes to have 8 characters including an
L in the 7th position.
Adding US* will force all new volumes to start with a US prefix.
```

Type

Select type of repository to change display icon to match repository function.
The basic choices are:

- Destruction
- Disaster Recovery
- Legal Hold
- Library
- Ordered
- Rack
- Scratch
- Transport
- Vault

Scratch Mode

Scratch Priority

Offsite

Primary

No Distribution

Internal

Sort Sequence

Force Simple Management

No Next Repository

Allow Deletes

De-assignment from Container

Empty Container

Do not slot if Container

Don not slot

Require Tag

Require Tag Reset

No re-move

Dissallow backward next move date changes

Reset Data Cluster

Confirm Container Contents

Move Container Contents

Late Threshold

Highwater offset

Movement Mode

Next Repository

Enable Slotting

Capacity

Capacity

- In Use
- Incoming
- Outgoing
- Minimum Scratch
- Scratch

Coordinates

Coordinates

- Latitude
- Longitude

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/master/repository_options?rev=1500312789

Last update: **2025/01/21 22:07**