

Repository Options

GUID

Allowable Volume ID's

When left blank, volumes with any allowable characters can be added to this repository. Filters can be added to force all new volumes added to conform to certain criteria.

Adding ??????L? will force all new volumes to have 8 characters including an L in the 7th position.

Adding US* will force all new volumes to start with a US prefix.

Type

Select type of repository to change display icon to match repository function.

The basic choices are:

-  Destruction
-  Disaster Recovery
-  Legal Hold
-  Library
-  Ordered
-  Rack
-  Scratch
-  Transport
-  Vault

Scratch Mode

- No Change
- Scratch
- Un-scratch

Scratch Priority

- Scratch selection priority (0=do not consider)

Offsite

- This repository is considered to be offsite when set to True.

Primary

- This repository is considered to be the Primary Repository when set to True.

No Distribution

- When picking a volume that is destined for this repository, confirm the movement when set to true.

Internal

- This Repository has an internal purpose and should not be displayed in all applications when set to True.

Sort Sequence

- The order in which this Repository will be displayed. (0=first, 255=last)

Force Simple Management

- When a Volume moves to this Repository always force [Simple Management](#) when set to True.

No Next Repository

- When set to True this Repository can be saved even though it may have no Next Repository.

Allow Deletes

- When set to True, Users with alter privileges can delete Volumes in the selected Repository.

Allow Overlaps

- When set to True this will allow internal overlapping Zone locations to be assigned to this Repository.

De-assignment from Container

- When set to True a confirmed Volume will be unassigned from a Container.

Empty Container

- When set to True all Volumes will be unassigned when confirmed.

Do not slot if Container

- When set to True it will add a “Do Not Slot” option to a Container when it is moved to this Repository.

Do not slot

- When set to True it will add a “Do Not Slot” option to any Volume when it is moved to this Repository.

Require Tag

- When set to True a Require a Tag value will be set for any Volume moving to this Repository.

Require Tag Reset

- When set to True a Require a Tag value to be confirmed before a Volume can be confirmed out of this Repository.

No re-move

- When set to True a Volume will not be allowed to be moved to another Repository until it is confirmed in this Repository.

Disallow backward next move date changes

- When set to True disallow any update to the move date of a Volume that is today or earlier.

Reset Data Cluster

- When set to True this will reset the Data Cluster of any Volume confirmed to this Repository.

Confirm Container Contents

- When set to True this will confirm the Container contents for this Repository.

Move Container Contents**Late Threshold**

Highwater offset

Movement Mode

Next Repository

Enable Slotting

Capacity

Capacity

- In Use
- Incoming
- Outgoing
- Minimum Scratch
- Scratch

Coordinates

Coordinates

- Latitude
- Longitude

From:

<https://docs.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

https://docs.tapetrack.com/master/repository_options?rev=1501189832

Last update: **2025/01/21 22:07**

