Repository

A Repository represents the general location of a Volume.

Repository-ID

A Repository-ID is a string of up to four alphanumeric characters and is permanently assigned at creation.

Each Repository-ID must be unique within its' Media type.

Description

A Repository object has a description field. This allows a user-friendly description of up to twenty alphanumeric characters to be associated with the Repository-ID.

States

Current Repository

The Current Location is the Repository the Volume is located at, or the Repository the Volume is moving from if the Volume is in a move status.

Target Repository

The target Location is the Repository the Volume is or should be moving to.

Scanned Location

The Scanned Location is the last location the Volume was confirmed at.

Dependencies

- Media type (parent)

Options

- allow_deletes
- allow_overlaps
- allowable_volume_ids
- capacity
- confirm_container_contents
- coordinates
- deassign_from_container
- disallow_backward_next_move_date_changes
- do_not_slot_if_container
- do_not_slot
- empty_container
- enable_slotting
- force_simple_management
- guid
- highwater_offset
- internal
- late_threshold
- move_container_contents
- movement_mode
- next_repository
- no_distribution
- no_next_repository
- no_remove
- offsite
- primary
- require_tag_reset
- require_tag
- reset_data_cluster
- retain_moving_slot
- scratch_mode
- scratch_priority
- sort_sequence
- type

Creating a Repository

A Repository Object can be created using:

- Adding and managing a Repository with TapeTrack TapeMaster.

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/object/repository?rev=1571264841

Last update: **2025/01/21 22:07**