Repository

A Repository represents the general location of a Volume.

Repository-ID

A Repository-ID is a string of up to four alphanumeric characters and is permanently assigned at creation.

Each Repository-ID must be unique within its' Media type.

Description

A Repository object has a Description field. This allows a user-friendly description of up to twenty alphanumeric characters to be associated with the Repository-ID.

Dependencies

- Media type (parent)

Options

- allow_deletes
- allow_overlaps
- allowable_volume_ids
- capacity
- confirm_container_contents
- coordinates
- deassign_from_container
- disallow_backward_next_move_date_changes
- do_not_slot_if_container
- do_not_slot
- empty_container
- enable_slotting
- force_simple_management
- guid
- highwater_offset
- internal
- late_threshold
- move_container_contents
- movement_mode
- next_repository

- no_distribution
- no_next_repository
- no_remove
- offsite
- primary
- require_tag_reset
- require_tag
- reset_data_cluster
- retain_moving_slot
- scratch_mode
- scratch_priority
- sort_sequence
- type

• Allow Deletes	2025/01/21 22:08	
• Allow Overlaps	2019/11/11 23:16	Scott Cunliffe
• Allowable Volume-ID's	2019/11/12 01:18	Scott Cunliffe
• Capacity	2019/04/18 02:10	Scott Cunliffe
• Confirm Container Contents	2019/04/11 02:53	Scott Cunliffe
• Coordinates	2025/01/21 22:08	
• De-Assign From Container	2026/08/27 07:43	
• Disallow Backward Next Move Date Changes	2019/04/11 01:51	Scott Cunliffe
• Do Not Slot	2019/04/09 03:46	Scott Cunliffe
• Do Not Slot If Container	2019/04/09 03:34	Scott Cunliffe
• Empty Container	2026/08/27 07:48	
• Enable Slotting	2019/04/18 01:39	Scott Cunliffe
• Force Simple Management	2025/01/21 22:08	
• GUID	2025/01/21 22:08	
• Highwater Offset	2026/08/12 03:51	
• Internal	2026/08/27 07:31	
• Late Threshold	2019/04/11 04:24	Scott Cunliffe
• Move Container Contents	2019/04/11 03:17	Scott Cunliffe
• Movement Mode	2025/01/21 22:08	
• Next Repository	2025/01/21 22:08	
• No Distribution	2026/08/27 07:26	
• No Next Repository	2019/11/11 23:15	Scott Cunliffe
• No Re-Move	2019/04/11 01:42	Scott Cunliffe
• Offsite	2025/01/21 22:08	
• Primary	2026/08/27 07:20	
• Require Tag	2019/11/11 23:18	Scott Cunliffe
• Require Tag Reset	2019/11/11 23:18	Scott Cunliffe
• Reset Data Cluster	2025/01/21 22:08	
• Retain Moving Slot	2025/01/21 22:08	
• Scratch Mode	2025/01/21 22:08	
• Scratch Priority	2019/04/08 01:13	Scott Cunliffe
• Show Built In Repositories	2025/01/21 22:08	

• Sort Sequence	2019/04/08 03:08 Scott Cunliffe
• Type	2019/04/07 23:59 Scott Cunliffe

Creating a Repository

A Repository Object can be created using:

- Adding and managing a Repository with TapeTrack TapeMaster.

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/object/repository?rev=1572994731

Last update: **2025/01/21 22:07**