

Allow Deletes

The [Repository Option](#) Allow Deletes allows the deletion of [Volumes](#) when they are located in this [Repository](#).



User requires Alter rights to delete Volumes

The screenshot shows the TapeTrack TapeMaster™ (GazillaByte LLC) interface. The main window displays the 'Volumes' table for the 'Los Angeles Data Center' and 'LTO Cartridge'. The table has columns for ID, Current Location, Target Location, Next Move, and Description. Below the table, it shows 'Total Items: 1,585'. At the bottom, there is a 'Repositories' section with icons for Gemtrac, Library, Transport, and Offsite Vault. The status bar at the bottom indicates 'Connection 127.0.0.1 uses AES 256 bit encryption'.

ID	Current Location	Target Location	Next Move	Description
000000L6	Offsite Vault	Library	Permanent	
000001L6	Library	Offsite Vault	Permanent	
000002L6	Library	Offsite Vault	Permanent	
000003L6	Library		Permanent	
000004L6	Library		Permanent	
000005L6	Library	Offsite Vault	Permanent	
000006L6	Library	Offsite Vault	Permanent	
000007L6	Library	Offsite Vault	Permanent	
000008L6	Library		Permanent	
000009L6	Library		Permanent	
000010L6	Library		Permanent	
000011L6	Offsite Vault		Permanent	
000012L6	Library		Permanent	
000013L6	Library		Permanent	
000014L6	Library		Permanent	
000015L6	Library		Permanent	

Allow Deletes Options

- True: Allow deletion of [Volumes](#).
- False: Disallow deletion of [Volumes](#).

It is recommended to keep Allow Deletes set to False when not needed to stop accidental

deletion of [Volumes](#).

[options](#), [repository options](#)

From:

<https://docs.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

https://docs.tapetrack.com/options/repository/allow_deletes?rev=1614126648

Last update: **2025/01/21 22:07**

