# Synchronization fields

The following fields can be set by synchronization:

| Field | Maximum Length | TapeTrack Field |
|---|---|---|
| CUSTOMER | 4 | Customer-ID |
| MEDIA | 4 | Media-ID |
| VOLUME | 10 | Volume-ID |
| REPOSITORY | 4 | Repository-ID |
| REPOSITORY_DESC | 20 | Description of Repository (used to set the Repository-ID) |
| SLOT | 10 | Slot for Repository. |
| DATACLUSTER | 256 | Data Cluster Value (Data Cluster must already exist) |
| DESCRIPTION | 256 | Volume Description (use program flag to set Extended Attributes) |
| MOVEDATE | 64 | Move Date (must have SetMoveDateFormat defined) |
| WRITETIME | 64 | Write Time (must have SetWriteTimeFormat defined) |
| CONTAINER | 20 | Fully qualified Container barcode |
| SYSTEM | 10 | System this Volume belongs to |
| ENCRYPTED | 10 | Is Volume encrypted (YES, NO, TRUE, FALSE) |
| SCRATCH | 10 | Is Volume scratch (YES, NO, TRUE, FALSE) |

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
**https://docs.tapetrack.com/sync/fields?rev=1555086671**

Last update: **2025/01/21 22:07**