

Barcode Interpretation Definition

A Barcode Interpretation Definition uses a string pattern to identify the barcodes format and handle the barcode accordingly.

The string pattern allows the dissection, translation or substitution of a barcode to identify [Customer-ID](#), [Media-ID](#) and [Volume-ID](#).



To view, add, remove or alter current Barcode Interpretation Definitions, open the [Barcode Administration](#) window in TapeMaster.

Examples

Barcode Pattern Definition **????.????.***

? translates to a single character * translates as a wild card and matches anything

Edit Barcode

Enabled	True
Barcode Description	Generic ?????.????.*
Scope	
Barcode Pattern	????[.]????[.]*
User Pattern	*
Range Start	
Range End	
Editing	
Edit Mask	00000000000000000000
Strip Characters	
Elements	
Customer-ID	
Use substring	True
Substring First Character	1
Substring Last Character	4
Media-ID	
Use substring	True
Substring First Character	6
Substring Last Character	9
Volume-ID	
Use substring	True
Substring First Character	11
Substring Last Character	20

OK Cancel

Barcode US01.CONT.CT100100

The filter will dissect the barcode to

- Customer-ID: US01
- Media-ID: CONT
- Volume-ID: CT100100

Barcode Pattern Definition *? ?*

Edit Barcode

Enabled

True

Barcode Description

Space Barcode Hash

Scope

Barcode Pattern

? ?

User Pattern

*

Range Start

Range End

Editing

Edit Mask

00000000000000000000

Strip Characters

Elements

Customer-ID

Use substring

False

Literal

Media-ID

Use substring

False

Literal

Volume-ID

Use substring

False

Literal

#

OK

Cancel

Volume-ID MONDAY WEEK ONE

The filter will hash the barcode to

- X-D8ED51DA

[technote](#), [barcode](#)

From:

<https://docs.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://docs.tapetrack.com/technote/barcode-interpretation-definition?rev=1603753996>

Last update: **2025/01/21 22:07**

