Disabling Journal And Volume History Entries

When Volume are added, moved or altered by default TapeTrack adds entries to the journal database and historical records for that volume.

If moves are required, for example moving a Volume from one location to another within your racking, journal records would cause the client to be charged for the move that is not billable. Temporarily turning off the journal and/or historical records can bypass this issue.

Disabling Journal Entries


Stop the Framework Server.



Backup Registry before making any alterations.

Do not edit the registry unless you are competent to do so.

Disabling the journal entries is achieved by adding an attribute to the registry entry for the Framework Sever. Once you have a current backup of the registry, navigate to `Computer\HKEY_LOCAL_MACHINE\SYSTEM\ControlSet001\Services\TMSS10SVC` in Registry Editor.



Double click on the `Image Path` to open up the `Edit String` window.

At the end of the Value data string, add the string required to disable the journal entries for the required Customer-ID's based on the following examples:

Disable journal entries for all Customers:

```
"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -J #DiSaBlE
```

Disable journal entries for all Customer US01:

```
"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -J US01
```

Disable journal entries for all Customers US01 and US03:

```
"C:\Program Files\TapeTrack\TapeTrack Framework Server\TMSS10Server.exe" -J "*(US01|US03)"
```

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/technote/journal_history?rev=1737334144

Last update: **2025/01/21 22:07**