


Restricting Which Volume-ID's Can Be Moved To A Repository.

TapeTrack allows the restriction of what volumes can be moved to a repository based on a pattern specified in the Repository properties.

Setting Volume-ID Restrictions

Open the required repository's properties and navigate to the Options tab.

Click in the field to the right of Allowable Volume-ID's and enter allowable volumes string pattern.



Restricting volume-ID patterns can be enforced using [TapeTrack string filters](#).

Character filters may be used alone or in combination to achieve the restricted volume-ID pattern required.

Example Patterns

Volume ID required	Filter Pattern	Example Volume-ID
Only volumes ending in L5	*L5	100001L5
Any volumes except those ending in L5	!*L5	100002L6
Volumes ending in L5 or starting with X-	*(L5 X-*)	X-2E8CA12F

Any attempt to move a volume with a non compliant volume-ID will cause an error and the move will be aborted.

Failed Operations

Error	Item	Time
Enter text here	Enter text here	Enter text here
 Disallowed Volume Serial. (see Media or Repository options)	000001L6	2018-06-21 12:39:06

Total Items1

☐ Display results that were OK

OK

From:
<https://docs.tapetrack.com/> - TapeTrack Documentation

Permanent link:
https://docs.tapetrack.com/technote/restricting_volumeid_by_repository?rev=1529549170

Last update: 2025/01/21 22:07

