Framework Server Command Line Arguments

The following server arguments can be passed to the Framework Server executable:

Argument	Type	Notes
-D	bool	Records a dump file if the server stops unexpectedly (Linux only)
-f	bool	Run the program in foreground more (Windows only)
-g	string	Location of the file GeoIP.dat, loads country code against active users
-h	string	Path to the directory containing the TapeTrack database
-H	string	Disables Volume history entries
-l	Integer	Log file format (0=append, 1=truncate, 2=timestamp, 3=stdout/stderr)
-J	string	Disable the journal file entries
-L	bool	Reload the database
-p	Integer/string	Port that TapeTrack will listen on. If string, the services file will be checked
-S	string	Syslogd host in format host:port (default localhost:514)
-r	bool	Allow a one time login to the 'tapemaster' User-ID with a blank password
-X	bool	Disable the replication sub-system
-V	bool	Print version and exit
-?	bool	Show help text

Example

To check what version of the Framework Server you have installed.

```
C:\>TMSS10Server -V

TapeTrack FrameWork Server. Compiled Jun 15 2020 @ 16:31:16
```

technote, server

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/technote/server_arguments

Last update: **2025/03/03 23:49**