

Setting Environmental Variables

The default behavior of TapeTrack programs can be changed by setting [environmental variable](#).

These [environmental variable](#) can be set using the following methods.

Windows Command Line

```
<sxh text;> set VARIABLE=VALUE </sxh>
```

Where VARIABLE is the [environmental variable](#) name, and VALUE is the [environmental variable](#) value.

PowerShell

To set an [environmental variable](#) in Windows PowerShell, use the env: command.

```
<sxh> $env:TMSSREPORTFORMAT = "CSV" </sxh>
```



Using PowerShell variables will have no effect on TapeTrack executables.

Using a variable \$TMSSREPORTFORMAT = "CSV" will not be interpreted as a Windows variable and will not be applied to the output.

Linux Shell

To set an [environmental variable](#) in the Linux operating system, use the export command.

```
<sxh plain;> export VARIABLE=VALUE </sxh>
```

Where VARIABLE is the [environmental variable](#) name, and VALUE is the [environmental variable](#) value.

You can also prepend the [environmental variable](#) to the command.

```
<sxh plain;> TMSSREPORTFORMAT=CSV TMSS10Inventory </sxh>
```

TapeTrack Config File

The TapeTrack Config File that is loaded when each [Desktop](#) and [Command Line Program](#) is initiated, it can also be used to set [environmental variable](#).

<sxh plain;>

```
variables = {  
    TMSSLEVELNAMES = "A,B,C";  
    TMSSNOLEVELSLOT = "1";  
};
```

</sxh>

From:
<https://docs.tapetrack.com/> - TapeTrack Documentation

Permanent link:
https://docs.tapetrack.com/technote/setting_environmental_variables?rev=1565651426

Last update: **2025/01/21 22:07**

