Setting Environmental Variables

The default behavior of TapeTrack programs can be changed by setting environmental variable.

These environmental variable can be set using the following methods.

Windows Command Line

<sxh text;> set VARIABLE=VALUE </sxh>

Where VARIABLE is the environmental variable name, and VALUE is the environmental variable value.

PowerShell

To set an environmental variable in Windows PowerShell, use the env: command.

<sxh> $env:TMSSREPORTFORMAT = “CSV” </sxh>



Using a PowerShell variable $TMSSREPORTFORMAT = “CSV” will not be interpreted as a Windows variable and, as such, will not be applied to the executable or output.

Linux Shell

To set an environmental variable in the Linux operating system, use the `export` command.

<sxh plain;> export VARIABLE=VALUE </sxh>

Where VARIABLE is the environmental variable name, and VALUE is the environmental variable value.

You can also prepend the environmental variable to the command.

<sxh plain;> TMSSREPORTFORMAT=CSV TMSS10Inventory </sxh>

TapeTrack Config File

The TapeTrack Config File that is loaded when each Desktop and Command Line Program is initiated, it can also be used to set environmental variable.

<sxh plain;>

```
variables = {
```

```
    TMSSLEVELNAMES = "A,B,C";
    TMSSNOLEVELSLOT = "1";
};
```

</sxh>

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/technote/setting_environmental_variables?rev=1565651497

Last update: **2025/01/21 22:07**