Setting Environmental Variables

The default behavior of TapeTrack programs can be changed by setting Environmental Variable.

These Environmental Variable can be set using the following methods.

Windows Command Line

<sxh text;> set VARIABLE=VALUE </sxh>

Where VARIABLE is the Environmental Variable name, and VALUE is the Environmental Variable value.

Windows PowerShell

To set an Environmental Variable in Windows PowerShell, use the $env: command.

<sxh> $env:TMSSREPORTFORMAT = “CSV” </sxh>

Where TMSSREPORTFORMAT is the Environmental Variable name, and CSV is the Environmental Variable value.



Using a Windows PowerShell variable $TMSSREPORTFORMAT = “CSV” will not be interpreted as a Windows variable and, as such, will not be applied to the executable or output.

Linux Shell

To set an Environmental Variable in the Linux operating system, use the `export` command.

<sxh plain;> export VARIABLE=VALUE </sxh>

Where VARIABLE is the Environmental Variable name, and VALUE is the Environmental Variable value.

You can also prepend the Environmental Variable to the command.

<sxh plain;> TMSSREPORTFORMAT=CSV TMSS10Inventory </sxh>

TapeTrack Config File

The TapeTrack Config File that is loaded when each Desktop and Command Line Program is initiated,

it can also be used to set Environmental Variable.

<sxh plain;>

```
variables = {
    TMSSLEVELNAMES = "A,B,C";
    TMSSNOLEVELSLOT = "1";
};
```

</sxh>

technote, variables, config, tapemaster, lite, checkpoint, linux

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/technote/setting_environmental_variables?rev=1626747035

Last update: **2025/01/21 22:07**