

Technical Note: TMSS10Volume Delete Examples

Files needed to delete Volumes from a defined list from nominated Customer-ID and Media-ID.

Example - Delete Volumes From CSV List

CSV File

```
<sxh> 100011L4 100012L4 100023L4 100025L4 100026L4 </sxh>
```

TTIDEF File

Set CSV delimiter to comma, Customer-ID to US01, Media-ID to LTO and extract Barcode value from column one.

```
<sxh> SetCSVDelimiter(",");
```

```
SetLiteral(CUSTOMER, "US04"); SetLiteral(MEDIA, "LTO");
```

```
Extract(BARCODE, 1, 8, 0);
```

```
</sxh>
```

Configuration File

Load Scanfile of Volume-ID's, traverse input file.

If Volume-ID is present in the Scanfile delete Volume, if not skip Volume.

```
<sxh> report = {
```

```
    format = "csv";
```

```
}; traversal = {
```

```
    scanfile= { file="default.ttidef"; };
```

```
    customer =
```

```
    (
```

```
        {
```

```
            id="*";
```

```
            media =
```

```
            (
```

```
                {
```

```
                    id="*";
```

```
        volume =  
        (  
            {  
                id="*";  
                scanfile = true;  
                skip=false;  
            },  
            {  
                id="*";  
                skip=true;  
            }  
        );  
    }  
};  
);
```

}; </sxh>

Command Line Syntax

Delete all volumes in volumes.csv from Customer-ID US01 and Media-ID LTO

<sxh> TMSS10VolumeDelete -S user:-password@server -c master.cfg -l -r * < volumes.csv </sxh>

From:

<https://docs.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://docs.tapetrack.com/technote/tmss10volumedelete?rev=1551741080>

Last update: **2025/01/21 22:07**

