

Technical Note: TMSS10VolumeDelete Examples

Files needed to delete Volumes from a defined list from nominated Customer-ID and Media-ID.

Files Required:

- CSV file of required Volumes
- Configuration file
- TTIDEF definition file

Example - Delete Volumes From CSV List

CSV File

```
<sxh> 100011L4 100012L4 100023L4 100025L4 100026L4 </sxh>
```

TTIDEF File

Set CSV delimiter to comma, Customer-ID to US01, Media-ID to LTO and extract Barcode value from column one.

```
<sxh> SetCSVDelimiter(",");
```

```
SetLiteral(CUSTOMER, "US04"); SetLiteral(MEDIA, "LTO");
```

```
Extract(BARCODE, 1, 8, 0);
```

```
</sxh>
```

Configuration File

Load Scanfile of Volume-ID's, traverse input file.

If Volume-ID is present in the Scanfile delete Volume, if not skip Volume.

```
<sxh> report = {
```

```
    format = "csv";
```

```
}; traversal = {
```

```
    scanfile= { file="default.ttidef"; };  
    customer =  
    (  
        {
```

```
{
  id="*";
  media =
  (
    {
      id="*";
      volume =
      (
        {
          id="*";
          scanfile = true;
          skip=false;
        },
        {
          id="*";
          skip=true;
        }
      );
    }
  );
};
```

```
}; </sxh>
```

Command Line Syntax

Delete all volumes in volumes.csv from Customer-ID US01 and Media-ID LTO

```
<sxh> TMSS10VolumeDelete -S user:-password@server -c master.cfg -l -r * < volumes.csv </sxh>
```

From:

<https://docs.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://docs.tapetrack.com/technote/tmss10volumedelete?rev=1551741175>

Last update: **2025/01/21 22:07**

