Technical Note: TMSS10VolumeDelete Examples

Files needed to delete Volumes from a defined list from nominated Customer-ID and Media-ID.

Example - Delete Volumes From CSV List

Files Required:

- CSV file of required Volumes
- Configuration file
- TTIDEF definition file

CSV File

CSV File **volumes.csv**

<sxh> 100011L4 100012L4 100023L4 100025L4 100026L4 </sxh>

TTIDEF File

TTIDEF File **default.ttidef**

Set CSV delimiter to comma, Customer-ID to US01, Media-ID to LTO and extract Barcode value from column one.

<sxh> SetCSVDelimiter(“,”);

SetLiteral(CUSTOMER, “US04”); SetLiteral(MEDIA, “LTO”);

Extract(BARCODE, 1, 8, 0);

</sxh>

Configuration File

Load Scanfile of Volume-ID's, traverse input file.
If Volume-ID is present in the Scanfile delete Volume, if not skip Volume.

Configuration File **master.cfg**

<sxh> report = {

```
  format = "csv";
```

}; traversal = {

```
scanfile= { file="default.ttidef"; };
customer =
(
   {
      id="*";
      media =
      (
         {
            id="*";
            volume =
            (
                {
                   id="*";
                   scanfile = true;
                   skip=false;
                },
                {
                   id="*";
                   skip=true;
                }
            );
         }
      );
   }
);
```

}; </sxh>

Command Line Syntax

Delete all Volumes in volumes.csv from Customer-ID US01 and Media-ID LTO

<sxh> TMSS10VolumeDelete -S user:-password@server -c master.cfg -l -r * < volumes.csv </sxh>

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/technote/tmss10volumedelete?rev=1551741856

Last update: **2025/01/21 22:07**