

TMSS10VolumeDelete Examples

Files needed to delete [Volumes](#) from a defined list from nominated [Customer-ID](#) and [Media-ID](#) using [TMSS10VolumeDelete](#).

Examples

Delete Volumes From CSV List

Delete [Volumes](#) from TapeTrack from a CSV list, using set [Customer-ID](#) and [Media-ID](#) Files Required:

- CSV file of required [Volumes](#)
- Configuration file
- TTIDEF definition file

CSV File

CSV File **volumes.csv**

```
<sxh> 100011L4 100012L4 100023L4 100025L4 100026L4 </sxh>
```

TTIDEF File

TTIDEF File **default.ttidef**

Set CSV delimiter to comma, [Customer-ID](#) to US01, [Media-ID](#) to LTO and extract Barcode value from column one.

```
<sxh> SetCSVDelimiter(",");
```

```
SetLiteral(CUSTOMER, "US04"); SetLiteral(MEDIA, "LTO");
```

```
Extract(BARCODE, 1, 8, 0);
```

```
</sxh>
```

Configuration File

Load Scanfile of [Volume-ID's](#), traverse input file.

If [Volume-ID](#) is present in the Scanfile delete [Volume](#), if not skip [Volume](#).

Configuration File **master.cfg**

```
<sxh> report = {
```

```
format = "csv";
```

```
}; traversal = {
```

```
scanfile= { file="default.ttidef"; };
customer =
(
  {
    id="*";
    media =
    (
      {
        id="*";
        volume =
        (
          {
            id="*";
            scanfile = true;
            skip=false;
          },
          {
            id="*";
            skip=true;
          }
        );
      }
    );
  }
);
```

```
}; </sxh>
```

Command Line Syntax

Delete all [Volumes](#) in volumes.csv from [Customer-ID](#) US01 and [Media-ID](#) LTO

```
<sxh> TMSS10VolumeDelete -S user:-password@server -c master.cfg -l -r * < volumes.csv </sxh>
```

[technote](#), [cli](#)

From:
<https://docs.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
<https://docs.tapetrack.com/technote/tmss10volumedelete?rev=1603681963>

Last update: **2025/01/21 22:07**

