

# Troubleshooter: Replication

Replication previously set up and running

Is the master server running

Yes

Is the replicant server running

Yes

Are the ports used by the master and replicant open and listening

Yes

No

Have your network staff open the required ports for inbound and outbound communications

Not sure

Checking master to replicant port access

Checking replicant to master port access

Stop the server Open config file, comment out replicant section and save file restart server in foreground mode, using the command in an administrative command line window `<sxh> TMSS10Server -f -h "%TMSS10DB%" -p 5010 </sxh>` Open another administrative command line window and execute the command `<sxh> netstat -na | find "5010" </sxh>` to check that the port is actively listening. If it is you will receive output similar to `<sxh> TCP 0.0.0.0:5010 0.0.0.0:0 LISTENING </sxh>`

No

Restart the replicant server using the Framework Server Helper, administrative command line or windows services

No

Not sure

From an administrative command line window on the master server run the command `TMSS10Ping`

Connection Successful

From an administrative command line window on the replicant server run the command TMSS10Ping

Connection Successful

Connection Unsuccessful

Connection Unsuccessful

Restart the master server using the Framework Server Helper, administrative command line or windows services

Replication not previously set up

From:

<https://docs.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://docs.tapetrack.com/troubleshooting/replication?rev=1531917674>

Last update: **2025/01/21 22:07**

