# Environmental Variables

The TapeTrack Desktop and Command Line Programs can be influenced in their behavior by setting environmental variables.

For more information on setting environmental variables see this Technical Note.

# Environmental Variables


- Setting Environmental Variables
- TMSS10BACK
- TMSS10DB
- TMSS10REPORTS
- TMSS10SCRIPTS
- TMSSAPILOGDIR
- TMSSATTRIBUTENOCASELOOKUP
- TMSSBARCODEPARSESPACEOK
- TMSSBEEP
- TMSSCMDSTRING
- TMSSCONFIGFILE
- TMSSCSVNOHEADER
- TMSSDESCRIPTIONTEXT
- TMSSDROPREPORT
- TMSSENVTRACE
- TMSSEXCELOUTPUTPATH
- TMSSINETD
- TMSSKERBEROS
- TMSSLEVELNAMES
- TMSSNOLEVELSLOT
- TMSSNOMD5
- TMSSPDFBLANKPAGETEXT
- TMSSPDFCOLORHDR
- TMSSPDFLOGOPATH
- TMSSPDFORIENTATION
- TMSSPDFOUTPUTPATH
- TMSSPDFPAGESIZE
- TMSSPRINTRAWINPUT
- TMSSPROGRESSDISABLE
- TMSSPWPATH
- TMSSRECONCILETEXT
- TMSSREPORTCOLUMNDELETE
- TMSSREPORTFORMAT

- TMSSREPORTHTMLLOGO
- TMSSREPORTTITLE
- TMSSSCANFILENOPARSE
- TMSSSCANFILEUNQUALIFIED
- TMSSSERVERPROXY
- TMSSSLACKICON
- TMSSSLACKNOTES
- TMSSSLACKONERROR
- TMSSSLACKURL
- TMSSSLACKUSER
- TMSSSTDERRDIR
- TMSSSTDERRNOCOLOR
- TMSSSTDERRTERMINAL
- TMSSUNQUALIFIEDVOLUME
- TMSSUSERINHERIT

# Linux Environmental Variables

- Linux Shared Objects

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
**https://docs.tapetrack.com/variable/start?rev=1574202070**

Last update: **2025/01/21 22:07**