TMSSAPILOGDIR

The Environmental Variable TMSSAPILOGDIR performs the following:

1. Enables TapeTrack low level API communications debugging.
2. Specifies the path of the directory where log files debugging files will be created.



Examples shown use fictional directories. Replace directory path with the actual directory you want to save debugging log files to on your own system

Example

<sxh> set TMSSAPILOGDIR=C:\Users\jsmith.GAZILLABYTE\Desktop\logs </sxh>

Example Output Using TMSS10Ping

<sxh> 10:14:46: TMSS10API_Init (API Version=Apr 20 2019 17:02:53) 10:14:46: TMSS10API_Connect: Server(localhost) Port(5000) 10:14:46: TMSS10API_Connect: Connection OK IP(127.0.0.1) 10:14:46: TMSS10API_Send: Function(Ping) Length(0) Flags(0) OptArgs(0) 10:14:46: TMSS10API_Send: RC(Request OK) Feedback(0) MiliSecs(0) Avail(0) Count(0) Length(0) 10:14:46: TMSS10API_Send: Function(Ping) Length(0) Flags(0) OptArgs(0) 10:14:46: TMSS10API_Send: RC(Request OK) Feedback(0) MiliSecs(0) Avail(0) Count(0) Length(0) 10:14:46: TMSS10API_Send: Function(Ping) Length(0) Flags(0) OptArgs(0) 10:14:46: TMSS10API_Send: RC(Request OK) Feedback(0) MiliSecs(0) Avail(0) Count(0) Length(0) 10:14:46: TMSS10API_Send: Function(Ping) Length(0) Flags(0) OptArgs(0) 10:14:46: TMSS10API_Send: RC(Request OK) Feedback(0) MiliSecs(0) Avail(0) Count(0) Length(0) 10:14:46: TMSS10API_Term </sxh>

See Also

Setting environmental variables

environmental variables, troubleshooting, logging

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
https://docs.tapetrack.com/variable/tmssapilogdir?rev=1579563206

Last update: **2025/01/21 22:07**