

TMSSLEVELNAMES

TMSSLEVELNAMES allows, via configuration files or command line interface, to map Zone level numbers to string values.

Example

Using TMSS10Inventory to display LTO volumes currently at repository OFFS from customer US04.

```
<sxh> TMSS10Inventory -S user:-password@server -V "US04.LTO.*@OFFS" </sxh>
```

Output

```
<sxh>
```

System: TapeTrack

Report Description: Inventory List

Report Notes: Customer(Nashville Data Center) Media Type(LTO Cartridge)
Production Time: Monday, June 18, 2018 - 11:25:39 (AUS Eastern Standard Time)
Report Width: 161 bytes

```
Seq. Barcode Location Repository Next Move Days Last Move GDup CDup Container ---
----- 1
US04.LTO.000001L5 GT1 [1.1] Offsite Vault [1] 2018-06-18 10:13 6 2
```

2	US04.LTO.000002L5	GT1 [1.2]	Offsite Vault [2]
2018-06-18 10:13	5	1	
3	US04.LTO.000003L5	GT1 [1.3]	Offsite Vault [3]
2018-06-18 10:13	5	1	
4	US04.LTO.000004L5	GT1 [1.5]	Offsite Vault [5]
2018-06-18 10:13	5	1	

```
-----
----- </sxh>
```

Setting TMSSLEVELNAMES to A, B, C before running TMSS10Inventory to change level names from 1, 2, 3 etc. TMSS10Inventory to display LTO volumes currently as repository OFFS from customer US04.



When setting variables makes sure there are no spaces. For example use **set TMSSLEVELNAMES=A,B,C** not **set TMSSLEVELNAMES = A,B,C**

```
<sxh>

set TMSSLEVELNAMES=A,B,C TMSS10Inventory -S user:-password@server -V "US04.LTO.*@OFFS"

</sxh>
```

Output

```
<sxh>
```

System: TapeTrack

Report Description: Inventory List

Report Notes: Customer(Nashville Data Center) Media Type(LTO Cartridge)
Production Time: Monday, June 18, 2018 - 11:31:27 (AUS Eastern Standard Time)
Report Width: 161 bytes

```
Seq. Barcode Location Repository Next Move Days Last Move GDup CDup Container  ---  -----
-----  1
US04.LTO.000001L5 GT1 [A.1] Offsite Vault [1] 2018-06-18 10:13 6 2
```

2	US04.LTO.000002L5	GT1 [A.2]	Offsite Vault [2]
2018-06-18 10:13	5	1	
3	US04.LTO.000003L5	GT1 [A.3]	Offsite Vault [3]
2018-06-18 10:13	5	1	
4	US04.LTO.000004L5	GT1 [A.5]	Offsite Vault [5]
2018-06-18 10:13	5	1	

```
-----  </sxh>
```

See Also

- [TMSSNOLEVELSLOT](#)
- [Setting environmental variables](#)

[environmental variables](#), [connecting](#)

From:
<https://docs.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
<https://docs.tapetrack.com/variable/tmsslevelnames?rev=1553740143>

Last update: **2025/01/21 22:07**

