# TMSSLEVELNAMES

The environmental variable TMSSLEVELNAMES allows, via Configuration files or Command Line Programs, to map Zone level numbers to string values.

## Example

Using TMSS10Inventory to display LTO Volumes currently at Repository OFFS from Customer US04.

<sxh> TMSS10Inventory -S user:-password@server -V “US04.LTO.*@OFFS” </sxh>

### Output

<sxh>

```
           System: TapeTrack
```

Report Description: Inventory List

```
     Report Notes: Customer(Nashville Data Center) Media Type(LTO Cartridge)
  Production Time: Monday, June 18, 2018 - 11:25:39 (AUS Eastern Standard
Time)
     Report Width: 161 bytes
```

Seq. Barcode Location Repository Next Move Days Last Move GDup CDup Container —— ———————- ———————————— ———————————— ———- ———- ———————- —- —- ———————- 1 US04.LTO.000001L5 GT1 [1.1] Offsite Vault [1] 2018-06-18 10:13 6 2

```
    2 US04.LTO.000002L5    GT1 [1.2]                       Offsite Vault [2]
2018-06-18 10:13    5    1
    3 US04.LTO.000003L5    GT1 [1.3]                       Offsite Vault [3]
2018-06-18 10:13    5    1
    4 US04.LTO.000004L5    GT1 [1.5]                       Offsite Vault [5]
2018-06-18 10:13    5    1
```

—— ———————- ———————————— ———————————— ———- ———- ———————- —- —- ———————- </sxh>

Setting TMSSLEVELNAMES to `A, B, C` before running TMSS10Inventory to change level names from 1, 2, 3 etc. TMSS10Inventory to display LTO Volumes currently as Repository OFFS from Customer US04.

<sxh> set TMSSLEVELNAMES=A,B,C TMSS10Inventory -S user:-password@server -V “US04.LTO.*@OFFS” </sxh>

### Output

<sxh>

```
           System: TapeTrack
```

Report Description: Inventory List

```
     Report Notes: Customer(Nashville Data Center) Media Type(LTO Cartridge)
  Production Time: Monday, June 18, 2018 - 11:31:27 (AUS Eastern Standard
Time)
     Report Width: 161 bytes
```

Seq. Barcode Location Repository Next Move Days Last Move GDup CDup Container —— ———————– ———————————— ———————————— ————- ————- ———————- —- —- ———————– 1 US04.LTO.000001L5 GT1 [A.1] Offsite Vault [1] 2018-06-18 10:13 6 2

```
    2 US04.LTO.000002L5    GT1 [A.2]                       Offsite Vault [2]
2018-06-18 10:13    5    1
    3 US04.LTO.000003L5    GT1 [A.3]                       Offsite Vault [3]
2018-06-18 10:13    5    1
    4 US04.LTO.000004L5    GT1 [A.5]                       Offsite Vault [5]
2018-06-18 10:13    5    1
```

—— ———————– ———————————— ———————————— ————- ————- ———————- —- —- ———————– </sxh>

## See Also

- TMSSNOLEVELSLOT
- Setting environmental variables

environmental variables, connecting, lite variable

From:
https://docs.tapetrack.com/ - **TapeTrack Documentation**

Permanent link:
**https://docs.tapetrack.com/variable/tmsslevelnames?rev=1565743113**

Last update: **2025/01/21 22:07**